

C SERIES**AIR/WATER - DUAL PURPOSE HOSE REELS****C SERIES :: REEL SPECIFICATIONS****SWIVEL**

- Two external fluid paths with machined from solid brass 90° full-flow NPT swivel inlets (Zinc plated steel swivels on HP models)
- Swivel Seals: NITRILE

DESIGN & STRUCTURE

- Compact two reel assembly for dual hose applications, each reel operates independently
- Guide arm adjusts to wall, floor & overhead positions
- Single expanded, 1/4" steel mounting base for increased stability & space efficiency
- One mounting pattern allow 1/2 the installation time required to install 2 reels at one station
- 1" solid steel axle & lubricated precision bearings for smooth rotation

RETRACTION

- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

• Air/Water Services	• Manufacturing Plants & Facilities
• Pneumatic Tools	• Maintenance, Repair & Operations
• Washdown	• Automotive & Fleet Service Centers
• Lubrication	
• Chemical Fluid Transfer	
• General Industrial	

**ACCESSORIZE YOUR REEL :: PG 52**

- O-Rings & Swivels
- Hoses
- Mounting Brackets
- Assorted Reel Accessories

COXREELS® C Series "Combination" spring driven hose reels are a combination of two hose reels in one compact assembly. They are perfect for applications in which two sources are needed to get the job done when space is a critical factor. The single mounting base creates stability and adds to the convenience of one mounting pattern. This series is also available in air hose/electrical cord combinations.

C SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
LOW PRESSURE						Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.		
C-LP-125-125	1/4"	1/2"	25	300	66	C-LPL-125-125	60	1
C-LP-135-135	1/4"	1/2"	35	300	67	C-LPL-135-135	60	1
C-LP-150-150	1/4"	1/2"	50	300	74	C-LPL-150-150	64	1
C-LP-325-325	3/8"	5/8"	25	300	67	C-LPL-325-325	60	2
C-LP-335-335	3/8"	5/8"	35	300	69	C-LPL-335-335	60	2
C-LP-350-350	3/8"	5/8"	50	300	78	C-LPL-350-350	64	2
C-LP-425-425	1/2"	3/4"	25	300	70	C-LPL-425-425	60	2
MEDIUM PRESSURE						Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum Temperature 250°F.		
C-MP-325-325	3/8"	11/16"	25	3,000	80	C-MPL-325-325	66	2
C-MP-335-335	3/8"	11/16"	35	3,000	86	C-MPL-335-335	68	2
C-MP-425-425	1/2"	13/16"	25	2,500	78	C-MPL-425-425	64	2
C-MP-430-430	1/2"	13/16"	30	2,500	84	C-MPL-430-430	66	2
HIGH PRESSURE						Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 250°F.		
C-HP-125-125	1/4"	9/16"	25	5,000	78	C-HPL-125-125	66	3
C-HP-135-135	1/4"	9/16"	35	5,000	84	C-HPL-135-135	68	3
C-HP-325-325	3/8"	11/16"	25	4,000	78	C-HPL-325-325	64	3
C-HP-330-330	3/8"	11/16"	30	4,000	82	C-HPL-330-330	66	3

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
1	10 1/2"	18 5/8"	17"	8"	9"	7"	8"
2	11 1/2"	18 5/8"	17"	8"	9"	7"	8"
3	12 5/8"	18 5/8"	17"	8"	9"	7"	8"

Overall Dimensions

Base

Mounting Pattern

