

September, 2008

## 3M™ Extended Liner Tape 450EK

### Product Description

3M™ Extended Liner Tapes have a liner that extends beyond the width of the adhesive to provide easy liner starting and removal. The liners (with the exception of 3M™ Extended Liner Tapes 450EK and 9934XL) are printed with the message, "Remove to Expose Adhesive".

### Product Features

- The extended liner provides a dry edge on each side of the tape for easy liner removal. Stated product widths include the dry edge of the liner.
- 3M™ Extended Liner Tape 450EK is ideal for pharmaceutical outsert attachment. 3M tape 450EK has the most tear resistant liner of these products. This release liner has stretch built into the paper making it tough and tear resistant.



### Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

### Typical Physical Properties

Property	Values	
Color	Clear	
Total Tape Thickness without liner	0.025 mm	1 mil
Adhesive	400 Acrylic	
Liner	70# White Extensible Kraft	
Liner Thickness	0.146 mm	5.6 mil
*Note	3M™ Adhesive 400 is a medium-firm acrylic pressure-sensitive adhesive system. It features high initial adhesion to a wide variety of materials and good shear holding power.	

### Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	2.2 N/cm	20 oz/in	ASTM D3330	Stainless Steel
Solvent Resistance	Medium/High			
UV Resistance	Excellent			

Relative High Temperature Operating Ranges		Test Condition
121 °C	250 °F	Short Term (minutes, hours)
82 °C	180 °F	Long Term (days, weeks)

Property: Relative High Temperature Operating Ranges

### Available Sizes

Property	Values	
Note	Subject to Minimum Order Requirements	
Maximum Length	548 m	600 yd
Available Width	25.4 mm	1 in

Table continued on next page

### Available Sizes (continued)

Property	Values	
Normal Slitting Tolerance	± 0.8 mm	± 1/32 in
Liner Extension Width (each side)	2.4 mm	3/32 in
Core Size (ID)	76.2 mm	3.0 in

### Handling/Application Information

#### Application Techniques

- Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure helps develop better adhesive contact and improve bond strength.
  - To obtain optimum adhesion, the bonding surfaces must be clean, dry, and well unified. Some typical surface cleaning solvents are isopropyl alcohol and heptane.\*
  - Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.
- \*Note: When using solvents, extinguish all ignition sources, including pilot lights, and follow the manufacturer's precautions and directions for use.

#### Storage and Shelf Life

24 months from date of manufacture when stored in original cartons at 70°F (21°C) and 50% relative humidity.

**Information**

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M’s control and uniquely within user’s knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer’s application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M’s option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

**Trademarks**

3M is a trademark of 3M Company.

**References**

**Safety Data Sheet (SDS)**

[https://www.3m.com/3M/en\\_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en\\_US&co=ptn&q=450EK](https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=450EK)

**Family Group**

	450EK	450XL	465XL	466XL	476XL	920XL	9925XL	9926XL	9934XL
Relative High Temperature Operating Ranges (°C) Test Condition: Short Term (minutes, hours)	121	121	121	121	65	121	65		66
Relative High Temperature Operating Ranges (°C) Test Condition: Long Term (days, weeks)	82	82	82	82	50	82	41		49
Color	Clear	Clear	Clear	Clear	Clear	Clear	Off-White Translucent	Clear	Clear - slight amber hue

Table continued on next page

## 3M™ Extended Liner Tape 450EK

### Family Group (continued)

	450EK	450XL	465XL	466XL	476XL	920XL	9925XL	9926XL	9934XL
Total Tape Thickness without liner (mm)	0.025	0.025	0.05	0.05	0.16	0.025	0.065	0.025	0.1
Adhesive	400 Acrylic	400 Acrylic	400 Acrylic	340 Acrylic	760 Rubber	400 Acrylic	770 Rubber	*400 Acrylic	*600
Liner	70# White Extensible Kraft	60# Kraft Glassine, Tan Green Printing	60# Densified Kraft Tan Paper Green Printing	62# Densified Kraft Off-White Paper Black Printing	43# Densified Kraft White Paper Red Printing	43# Densified Kraft White Paper Red Printing	43# Densified Kraft White Paper Black Printing	43# Densified Kraft White Paper Red Printing	60# Semi-bleached Kraft
Liner Thickness (mm)	0.146	0.09	0.09	0.11	0.08	0.065	0.05	0.065	0.09

### ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

