



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 31-4059-7
Issue Date: 05/16/25

Version Number: 7.01
Supersedes Date: 10/07/24

SECTION 1: Identification

1.1. Product identifier

3M™ Industrial Degreaser Concentrate (Product No. 26, 3M™ Chemical Management Systems)

Product Identification Numbers

ID Number	UPC	ID Number	UPC
61-0000-6352-1		61-0000-6353-9	
61-0000-6388-5		61-0000-6389-3	
61-0000-6415-6		70-0715-9446-2	0-48011-29664-7
70-0715-9447-0	0-48011-29678-4	70-0715-9448-8	0-48011-29665-4
70-0715-9449-6	0-48011-29677-7	70-0716-5884-6	
70-0716-8360-4	0-48011-29664-7	70-0716-8361-2	0-48011-29678-4
70-0716-8362-0	0-48011-29665-4	70-0716-8363-8	0-48011-29677-7

7000053107, 7100040679, 7100051876, 7010385279, 7100122450, 7010385380, 7010364132, 7100149393, 7010328505, 7010328513, 7010385967, 7010309289

1.2. Recommended use and restrictions on use

Recommended use

Removes petroleum-based grease and oil, animal fats, food soils and heavy dirt buildup. Can be used in industrial plants, transportation and auto facilities, schools, hospitals and other facilities to clean a variety of surfaces., Hard Surface Cleaner

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Commercial Branding and Transportation Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 4.

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Reproductive Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Health Hazard |

Pictograms



Hazard Statements

Combustible liquid.

Causes severe skin burns and eye damage.

Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves, protective clothing, and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

7% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	68154-99-4	25 - 35 Trade Secret *
Aminomethyl Propanol	124-68-5	20 - 30 Trade Secret *
Water	7732-18-5	20 - 30 Trade Secret *
Ethylhexyloxyethanol	1559-35-9	5 - 10 Trade Secret *
Quaternary Ammonium Chloride	68610-19-5	5 - 10 Trade Secret *
2-Methylamino-2-methyl-1-propanol	27646-80-6	< 3 Trade Secret *
Diethylene Glycol Mono(2-Ethylhexyl) Ether	1559-36-0	1 - 2 Trade Secret *
Isopropanol	67-63-0	< 2 Trade Secret *
Fragrance Compound	Trade Secret*	< 1 Trade Secret *
Acid Red 52	3520-42-1	< 0.05 Trade Secret *
Acid Violet 12	6625-46-3	< 0.01 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. This product is not intended to be used without prior dilution as specified on the product label. Grounding or safety shoes with electrostatic dissipating soles (ESD) are not required with a chemical dispensing system. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Isopropanol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
Isopropanol	67-63-0	OSHA	TWA:980 mg/m3(400 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

NOTE: When used with a chemical dispensing system as directed, special ventilation is not required.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

NOTE: When used with a chemical dispensing system as directed, eye contact with the concentrate is not expected to occur. The following protection(s) are recommended if the product is not used with a chemical dispensing system or if there is an accidental release, wear protective eye/face protection. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

NOTE: When used with a chemical dispensing system as directed, skin contact with the concentrate is not expected to occur. If product is not used with a chemical dispensing system or if there is an accidental release:

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary.

If product is not used with a chemical dispensing system or if there is an accidental release:

Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended:

Apron - polymer laminate

Respiratory protection

NOTE: When used with a chemical dispensing system as directed, respiratory protection is not required.

If product is not used with a chemical dispensing system or if there is an accidental release:

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Red

Odor

Fresh Odor, Moderate Detergent

Odor threshold

No Data Available

pH

10.5 - 11.5 Units not avail. or not appl.

Melting point

No Data Available

Boiling Point

> 147 °F

Flash Point

147 °F [*Test Method*:Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

27 mmHg [@ 20 °C] [*Ref Std*:AIR=1]

Vapor Density

No Data Available

Density

No Data Available

Specific Gravity

0.97 - 1.01 [*Ref Std*:WATER=1]

Solubility in Water

Complete

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

48 centipoise

Molecular weight

Not Applicable

Volatile Organic Compounds

25 - 35 % weight [*Test Method*:Estimated]

Percent volatile

No Data Available

VOC Less H₂O & Exempt Solvents

350 - 450 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong acids
Strong oxidizing agents
Reducing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Aminomethyl Propanol	Dermal	Rabbit	LD50 > 2,000 mg/kg
Aminomethyl Propanol	Ingestion	Rat	LD50 2,900 mg/kg
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	Dermal	Professional judgement	LD50 2,000 mg/kg
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	Ingestion	Rat	LD50 2,414 mg/kg
Ethylhexyloxyethanol	Dermal	Rabbit	LD50 2,120 mg/kg
Ethylhexyloxyethanol	Ingestion	Rat	LD50 4,674 mg/kg
Quaternary Ammonium Chloride	Ingestion	Professional judgement	LD50 estimated to be 300 - 2,000 mg/kg
2-Methylamino-2-methyl-1-propanol	Ingestion	Professional judgement	LD50 estimated to be 300 - 2,000 mg/kg
Isopropanol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropanol	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropanol	Ingestion	Rat	LD50 4,710 mg/kg
Diethylene Glycol Mono(2-Ethylhexyl) Ether	Dermal	Rabbit	LD50 2,310 mg/kg
Diethylene Glycol Mono(2-Ethylhexyl) Ether	Ingestion	Rat	LD50 6,900 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aminomethyl Propanol	Rabbit	Irritant
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	Professional judgement	Irritant
Ethylhexyloxyethanol	Rabbit	Irritant
Quaternary Ammonium Chloride	Professional judgement	Corrosive
2-Methylamino-2-methyl-1-propanol	Professional judgement	Corrosive
Isopropanol	Multiple animal species	No significant irritation
Diethylene Glycol Mono(2-Ethylhexyl) Ether	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Aminomethyl Propanol	Rabbit	Corrosive
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	Professional judgement	Severe irritant
Ethylhexyloxyethanol	Rabbit	Severe irritant
Quaternary Ammonium Chloride	Professional judgement	Corrosive

	nt	
2-Methylamino-2-methyl-1-propanol	Professional judgement	Corrosive
Isopropanol	Rabbit	Severe irritant
Diethylene Glycol Mono(2-Ethylhexyl) Ether	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
Aminomethyl Propanol	Guinea pig	Not classified
Ethylhexyloxyethanol	Guinea pig	Not classified
Isopropanol	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aminomethyl Propanol	In Vitro	Not mutagenic
Aminomethyl Propanol	In vivo	Not mutagenic
Ethylhexyloxyethanol	In Vitro	Not mutagenic
2-Methylamino-2-methyl-1-propanol	In Vitro	Not mutagenic
Isopropanol	In Vitro	Not mutagenic
Isopropanol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Isopropanol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Aminomethyl Propanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Aminomethyl Propanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	37 days
Aminomethyl Propanol	Dermal	Not classified for development	Rat	NOAEL 300 mg/kg/day	during gestation
Aminomethyl Propanol	Ingestion	Toxic to development	Rat	NOAEL 100 mg/kg/day	premating into lactation
Ethylhexyloxyethanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
Ethylhexyloxyethanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	5 weeks
Ethylhexyloxyethanol	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	premating into lactation
Isopropanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropanol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropanol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aminomethyl Propanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Ethylhexyloxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Quaternary Ammonium Chloride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-Methylamino-2-methyl-1-propanol	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not Available	
Isopropanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropanol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Diethylene Glycol Mono(2-Ethylhexyl) Ether	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aminomethyl Propanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 23 mg/kg/day	90 days
Aminomethyl Propanol	Ingestion	blood eyes kidney and/or bladder	Not classified	Dog	NOAEL 2.8 mg/kg/day	1 years
Ethylhexyloxyethanol	Ingestion	liver hematopoietic system nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	5 weeks
Isopropanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropanol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropanol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Reproductive toxicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient

Ethylhexyloxyethanol (CAS NO SEQ548L1)
Isopropanol

C.A.S. No

1559-35-9
67-63-0

% by Wt

Trade Secret 5 - 10
Trade Secret < 2

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 31-4059-7

Version Number: 7.01

Issue Date: 05/16/25

Supersedes Date: 10/07/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com