



PIG™ Latching Drum Lid with Fusible Plugs

DRM1065 For 55 gal. Steel Drums, FM-Approved, Bolt-Ring

The only latching lid that meets NFPA 30 venting requirements helps you safely contain and lock flammable materials in a 55-gallon steel drum.

- The only latching lid that satisfies NFPA 30 venting requirements
- In a fire, 2" and 3/4" FM Approved nylon plugs melt to vent pressure and prevent drum bursting
- Ideal for safe storage of flammable or combustible solids such as used rags and absorbents
- Latching handle easily opens and closes with one hand
- Nitrile gasket and locking mechanism seal lid to help reduce vapor emissions
- Easy-access lid closes securely to help you meet haz-waste regs
- Hinge stops keep funnel lid upright when open
- Durable, chemical-resistant powder coat helps ensure long service life
- Lockable latch helps prevent unauthorized access
- Hinge pin is made for easy lid removal without loosening band around drum



Item#	Description	Dimensions	Weight
DRM1065-YW	Yellow,	23.25" W x 26.75" L x 4.375" H	25 lbs.
DRM1065-RD	Red,	23.25" W x 26.75" L x 4.375" H	25 lbs.
DRM1065-BK	Black,	23.25" W x 26.75" L x 4.375" H	25 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM1065-YW	Yellow,	59.1cm W x 67.9cm L x 11.1cm H	11.3 kg
DRM1065-RD	Red,	59.1cm W x 67.9cm L x	11.3 kg

		11.1cm H	
DRM1065-BK	Black,	59.1cm W x 67.9cm L x 11.1cm H	11.3 kg

Specifications

Special Feature	FM-Approved
Style	Hinged Lid w/ One-Hand Latch
Use With	55 gal. Steel Drums
Dimensions	23.25" W x 26.75" L x 4.375" H
Drum Mounting	Bolt-Ring
Drum Size	55 gal.
Drum Type	Steel Drum
Sold as	1 per box
Weight	25 lbs.
NSN (National Stock Number)	DRM1065-BK-8110-01-595-7372
NSN (National Stock Number)	DRM1065-RD-8110-01-595-7372
NSN (National Stock Number)	DRM1065-YW-8110-01-595-7372
# per Pallet	23
Composition	Lid - Steel Gasket - Nitrile Bungs - Nylon
Padlockable	Padlockable w/ .25" Shackle
UNSPSC	24112112
Pigalog® Page Number	<u>Page 304</u>

Metric Equivalent

Dimensions	59.1cm W x 67.9cm L x 11.1cm H
Weight	11.3 kg

Technical Information

Certifications, Approvals and Ratings

FM Approved,NFPA Code 30

Technical Documents

- Nitrile gasket for PIG® Drum lids and funnels
- PIG Latching Drum Lid (Steel) Instructions
- 29 CFR 1910.106(e)(2)(i)
- 29 CFR 1910.22(a)
- 40 CFR 261.4
- 40 CFR 262.15

40 CFR 262.16(b)(2)(iii)

40 CFR 262.17(a)(1)(iv)

40 CFR 264.1086(c)(1)(ii)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com