

PIG® DrainBlocker® Curb-Style Drain Cover



PLR510 Ideal For Emergency Response, For Curb-Style Drains Up to 114" x 12"

Thin, moldable DrainBlocker Drain Cover seals to guard a vertical storm drain or inlet or contain washdown spray.

- Thin, pliable drain cover can form into an S-shape to block liquids from vertical storm drains
- Tear-resistant polypropylene top withstands repeated use
- Super-sealing urethane bottom layer creates a tight seal on curved or face-opening drains
- Reusable cover resists chemicals, oils and detergents
- High-visibility green makes it easy to confirm protection from a distance
- Ideal for power washing and other spill-prone operations
- Cost-effective alternative to inflatable plugs and other specialized equipment
- For drains with vertical and horizontal openings, this cover should be used with a DrainBlocker Drain Cover (sold separately)



Specifications

Traffic	Non-Weight Bearing
Use With	Curb-Style Drains Up to 114" x 12"
Color	Green
Dimensions	18" W x 120" L x 0.1" H
Drain Shape	Curb-Style
Drain Size	Up to 114" x 12"
Ideal For	Emergency Response
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes
Storage Temp Range	Store from 0°F to 120°F
Temperature Limit	Works from 0° to 160°F up to 12 months
Sold as	1 each
Weight	11 lbs.
New Pig Patent	Patent Pending
# per Pallet	50

Composition	Top - Polypropylene Bottom - Polyurethane
UNSPSC	40141739
UV Resistant	No
Pigalog® Page Number	<u>Page 172</u>

Metric Equivalent

Dimensions	45.7cm W x 3m L x 2.5mm H
Weight	5 kg

Technical Information

Technical Documents

[PIG Washblocker Strip and PIG Drainblocker Curb-Style Drain Cover](#)

[PIG® DRAINBLOCKER® Curb-Style Drain Cover Instructions](#)

[Urethane Use, Care and Storage](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](#) • hothogs@newpig.com