

FILTERS, REGULATORS & LUBRICATORS

29 Series Integral Assemblies

Filter / Regulator - Lubricator



Filter - Regulator - Lubricator



Specifications

Proof Pressure: **220 PSI**
 Max Operating Pressure: **145 PSI**
 Maximum Operating Temp.:
 Plastic Bowl: **140° F**
 Metal Bowl: **150° F**
 Ambient & Fluid Temp: **32° F to 140° F**
 Nominal Filtration Rating¹:
 Standard: **40 Micron**
 Optional: **5, 20 Micron**

Materials:
 Plastic Bowl: **Polycarbonate**
 Metal Bowl²: **Aluminum**
 Body: **Aluminum**
 Filter Element: **Polypropylene**
 Bowl Guard³: **Steel**
 Regulating Range⁴: **5 PSI - 120 PSI**
 Regulator Construction: **Relieving Type**
 Gauge⁵: **Square**

FEATURES

- ◆ Modular design.
- ◆ Metal bowl option.
- ◆ Low pressure spring option.
- ◆ 40 micron element standard.
- ◆ 5, 20 micron element option.

¹Standard: 40 µm - Options: 5, 20 µm

²Metal Bowl is available on all Series

³No bowl guard on Series 2D, 2T

⁴Option: Low Pressure Regulating Range 5 - 35 psi

⁵Option: Round gauge

Ordering Information:

Pipe Size	Max. Flow	Filter/Regulator	Lubricator	Manual Model	Auto Drain Model
1/8"	20	29-2C18-00D	29-2L18	29-2D18-00	29-2D18-00D
1/8"	20	29-2C18-00DM	29-2L18-M		29-2D18-00DM
1/4"	20	29-2C14-00D	29-2L14	29-2D14-00	29-2D14-00D
1/4"	20	29-2C14-00DM	29-2L14-M		29-2D14-00DM
1/4"	60	29-3C14-00D	29-3L14	29-3D14-00	29-3D14-00D
1/4"	60	29-3C14-00DM	29-3L14-M		29-3D14-00DM
3/8"	60	29-3C38-00D	29-3L38	29-3D38-00	29-3D38-00D
3/8"	60	29-3C38-00DM	29-3L38-M		29-3D38-00DM
3/8"	106	29-4C38-00D	29-4L38	29-4D38-00	29-4D38-00D
3/8"	106	29-4C38-00DM	29-4L38-M		29-4D38-00DM
1/2"	106	29-4C12-00D	29-4L12	29-4D12-00	29-4D12-00D
1/2"	106	29-4C12-00DM	29-4L12-M		29-4D12-00DM

Ordering Information:

Pipe Size	Max. Flow	Filter	Regulator	Lubricator	Manual Model	Auto Drain Model
1/8"	20	29-2F18-0D	29-2R18-0	29-2L18	29-2T18-00	29-2T18-00D
1/8"	20	29-2F18-0DM	29-2R18-0	29-2L18-M		29-2T18-00DM
1/4"	20	29-2F14-0D	29-2R14-0	29-2L14	29-2T14-00	29-2T14-00D
1/4"	20	29-2F14-0DM	29-2R14-0	29-2L14-M		29-2T14-00DM
1/4"	70	29-3F14-0D	29-3R14-0	29-3L14	29-3T14-00	29-3T14-00D
1/4"	70	29-3F14-0DM	29-3R14-0	29-3L14-M		29-3T14-00DM
3/8"	70	29-3F38-0D	29-3R38-0	29-3L38	29-3T38-00	29-3T38-00D
3/8"	70	29-3F38-0DM	29-3R38-0	29-3L38-M		29-3T38-00DM
3/8"	110	29-4F38-0D	29-4R38-0	29-4L38	29-4T38-00	29-4T38-00D
3/8"	110	29-4F38-0DM	29-4R38-0	29-4L38-M		29-4T38-00DM
1/2"	140	29-4F12-0D	29-4R12-0	29-4L12	29-4T12-00	29-4T12-00D
1/2"	140	29-4F12-0DM	29-4R12-0	29-4L12-M		29-4T12-00DM
3/4"	175	29-5F34-0D	29-5R34-0	29-5L34	29-5T34-00	29-5T34-00D
3/4"	175	29-5F34-0DM	29-5R34-0	29-5L34-M		29-5T34-00DM
1"	175	29-5F10-0D	29-5R10-0	29-5L10	29-5T10-00	29-5T10-00D
1"	175	29-5F10-0DM	29-5R10-0	29-5L10-M		29-5T10-00DM

Accessory Information:

Description	Model
Mounting Bracket Set for Filter and Lubricator	29-2FLMB 29-3FLMB 29-4FLMB 29-5FLMB
Mounting Bracket Set for Regulator and Filter Regulator	29-2RMB 29-3RMB 29-4RMB 29-5RMB



Accessory Information:

Description	Model
Spacer with Type "T" Bracket for FRL Units	29-2MMB 29-3MMB 29-4MMB 29-5MMB
Aluminum Transition Plate Square Gauge to Round Gauge	29-RTP14 29-RTP18

For All Your Pneumatic Accessory Needs • www.coilhose.com
 EAST: 19 Kimberly Road, East Brunswick, NJ 08816 • 732.390.8480
 WEST: 1730 NE Miller Street, McMinnville, OR 97128 • 503.434.5964

