

842/4 Bits, 5 x 89 mm

Bits for Hexagon Socket Screws



EAN:	4013288155955	Size:	89x7x7 mm
Part number:	05059682001	Weight:	22 g
Article number:	842/4	Country of origin:	CZ
		Customs tariff number:	82079030

- For socket head screws
- Ductile and tough for hard materials
- Hexagon ballpoint for work in difficult installation situations
- 1/4" hexagon drive (Wera connecting series 4)
- Suitable for AEG, ARO, Atlas-Copco, Biax, Black & Decker, Bosch, Buckeye Tools etc.

Tough viscous Wera bits for hexagon socket screws and universal use. The ballpoint drive profile means that it is possible to swivel the tool axis away from the screwdriving axis, thus enabling "round the corner" screwdriving. 1/4" hexagon, suitable for holders as per DIN ISO 1173-F 6.3.

Web link

https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_hexagon_socket_screws_842_4.html

Wera - 842/4
05059682001 - 4013288155955

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Ball tip







The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

Tough-absorbing bits



Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.

Further versions in this product family:

				
	mm	inch	mm	inch
05059680001	3.0		89	3 1/2
05059681001	4.0		89	3 1/2
05059682001	5.0		89	3 1/2
05059683001	6.0		89	3 1/2
05380124001		3/32	89	3 1/2
05380125001		7/64	89	3 1/2
05380126001		1/8	89	3 1/2
05380127001		9/64	89	3 1/2
05380128001		5/32"	89	3 1/2
05380129001		3/16"	89	3 1/2
05380130001		7/32"	89	3 1/2
05380131001		1/4	89	3 1/2

Web link

https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_hexagon_socket_screws_842_4.html

Wera - 842/4

05059682001 - 4013288155955

Wera Werkzeuge GmbH

Korzerter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de