



JDP-20EVST-230, 1-1/2" Drilling Capacity, 2HP, 230V 3Ph with Forward and Reverse Tapping capability

Product Images



Description

JET Electronic Variable Speed Drill Presses offer variable spindle speed rates between 65 and 2000 RPM for a wide variety of applications, supported by high quality ball bearings. Designed to permit continuous speed adjustment - even during operation. Forward and reverse tapping capabilities, an emergency stop, and a heavy-duty casted head are but a few of the features JET includes to enhance overall use and accuracy. CSA/CUS Certified.

Additional Information

| | |
|--|------------------------------|
| SKU | 354225 |
| Base Dimensions (In.) | 27 x 19 |
| Column Diameter (In.) | 4-1/2 |
| Distance Column to Spindle (In.) | 10-7/16 |
| Drilling Capacity Cast Iron (In.) | 1-1/2 |
| Drilling Capacity Mild Steel (In.) | 1-3/8 |
| Drills to Center of Circle (In.) | 20 |
| Motor (HP) | 2 HP, 230V 3ph |
| Overall Dimensions (L x W x H) (In.) | 38.18 x27.16 x 79.52 |
| Prop 65 | Cancer and Reproductive Harm |
| Range of Spindle Speeds (RPM) | 65-540 /245- 2,000 |
| Spindle Distance to Base (In.) | 44-1/2 |
| Spindle Distance to Table (Max.) (In.) | 30-1/4 |
| Spindle Taper (In. x TPI) | MT-3 |
| Spindle Travel (In.) | 6 |
| Style (Type) | Variable Speed |
| T-Slot Centers (In.) | 7-7/16 |
| Table Size (L x W) (In.) | 22x18-3/4 |
| Table Travel (In.) | 20 |
| Tapping Capacity Cast Iron (In.) | 7/8 |
| Tapping Capacity Mild Steel (In.) | 3/4 |
| Weight (Lbs.) | 792 |
| Work Table Weight Capacity (Lbs.) | 154 |

