



## Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 43-0450-7 | <b>Version Number:</b>  | 2.00     |
| <b>Issue Date:</b>     | 05/13/25  | <b>Supersedes Date:</b> | 04/14/22 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Abrasive Products, Cubitron™ II, 784F Discs, PSA and Hookit™

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Abrasive Product, For industrial/occupational use only. Not for consumer sale or use.

#### 1.3. Supplier's details

|                      |                                         |
|----------------------|-----------------------------------------|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Abrasive Systems Division               |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### 2.2. Label elements

##### Signal word

Not applicable.

##### Symbols

Not applicable.

##### Pictograms

Not applicable.

50% of the mixture consists of ingredients of unknown acute oral toxicity.

50% of the mixture consists of ingredients of unknown acute dermal toxicity.

67% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

| <b>Ingredient</b>                                                   | <b>C.A.S. No.</b> | <b>% by Wt</b> |
|---------------------------------------------------------------------|-------------------|----------------|
| Cured Resin                                                         | Mixture           | 15 - 55        |
| Cloth Backing                                                       | Mixture           | 10 - 50        |
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | 1344-28-1         | 10 - 35        |
| Inorganic Fluoride 1                                                | 14075-53-7        | 2 - 20         |
| Filler 1                                                            | 1317-65-3         | 1 - 15         |
| Inorganic Fluoride 2                                                | 13775-53-6        | < 15           |
| Hookit™ Backing                                                     | Mixture           | < 10           |
| PSA Backing                                                         | Mixture           | < 10           |
| Filler 2                                                            | 13983-17-0        | < 5            |
| Inorganic Fluoride 3                                                | 15096-52-3        | < 5            |
| Paper liner                                                         | Mixture           | < 5            |
| Quartz Silica                                                       | 14808-60-7        | < 0.5          |
| Titanium Dioxide                                                    | 13463-67-7        | < 0.5          |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### **If Swallowed:**

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide

Carbon dioxide

#### Condition

During Combustion

During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Not applicable.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not breathe thermal decomposition products. For industrial/occupational use only. Not for consumer sale or use. Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Avoid release to the environment. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient                                                                            | C.A.S. No. | Agency | Limit type                                                                            | Additional Comments            |
|---------------------------------------------------------------------------------------|------------|--------|---------------------------------------------------------------------------------------|--------------------------------|
| Filler 1                                                                              | 1317-65-3  | OSHA   | TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup> |                                |
| Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles  | 1317-65-3  | ACGIH  | TWA(inhalable particulates):10 mg/m <sup>3</sup>                                      |                                |
| Particles (insoluble or poorly soluble) not otherwise specified, respirable particles | 1317-65-3  | ACGIH  | TWA(respirable particles):3 mg/m <sup>3</sup>                                         |                                |
| Aluminum, insoluble compounds                                                         | 1344-28-1  | ACGIH  | TWA(respirable fraction):1 mg/m <sup>3</sup>                                          | A4: Not class. as human carcin |
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous)                   | 1344-28-1  | OSHA   | TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup> |                                |

|                                                                                       |            |       |                                                                                                                                                     |                                |
|---------------------------------------------------------------------------------------|------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|
| Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles  | 1344-28-1  | ACGIH | TWA(inhalable particulates):10 mg/m3                                                                                                                |                                |
| Particles (insoluble or poorly soluble) not otherwise specified, respirable particles | 1344-28-1  | ACGIH | TWA(respirable particles):3 mg/m3                                                                                                                   |                                |
| Titanium Dioxide                                                                      | 13463-67-7 | ACGIH | TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3                                                         | A3: Confirmed animal carcin.   |
| Titanium Dioxide                                                                      | 13463-67-7 | OSHA  | TWA(as total dust):15 mg/m3                                                                                                                         |                                |
| FLUORIDES                                                                             | 13775-53-6 | ACGIH | TWA(as F):2.5 mg/m3                                                                                                                                 | A4: Not class. as human carcin |
| FLUORIDES                                                                             | 13775-53-6 | OSHA  | TWA(as F):2.5 mg/m3;TWA(as dust):2.5 mg/m3                                                                                                          |                                |
| Filler 2                                                                              | 13983-17-0 | ACGIH | TWA(inhalable fraction):1 mg/m3                                                                                                                     | A4: Not class. as human carcin |
| Quartz Silica                                                                         | 14808-60-7 | ACGIH | TWA(respirable fraction):0.025 mg/m3                                                                                                                | A2: Suspected human carcin.    |
| Quartz Silica                                                                         | 14808-60-7 | OSHA  | TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.) |                                |
| Aluminum, insoluble compounds                                                         | 15096-52-3 | ACGIH | TWA(respirable fraction):1 mg/m3                                                                                                                    | A4: Not class. as human carcin |
| FLUORIDES                                                                             | 15096-52-3 | ACGIH | TWA(as F):2.5 mg/m3                                                                                                                                 | A4: Not class. as human carcin |
| FLUORIDES                                                                             | 15096-52-3 | OSHA  | TWA(as F):2.5 mg/m3;TWA(as dust):2.5 mg/m3                                                                                                          |                                |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

### 8.2.2. Personal protective equipment (PPE)

**Eye/face protection**

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

**Respiratory protection**

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance****Physical state**

Solid

**Color**

Red

**Odor**

Slight Polymeric

**Odor threshold***Not Applicable***pH***Not Applicable***Melting point***Not Applicable***Boiling Point***Not Applicable***Flash Point***Not Applicable***Evaporation rate***Not Applicable***Flammability (solid, gas)**

Not Classified

**Flammable Limits(LEL)***Not Applicable***Flammable Limits(UEL)***Not Applicable***Vapor Pressure***Not Applicable***Vapor Density***Not Applicable***Density***Not Applicable***Specific Gravity***Not Applicable***Solubility in Water***Not Applicable***Solubility- non-water***Not Applicable***Partition coefficient: n-octanol/ water***Not Applicable***Autoignition temperature***Not Applicable***Decomposition temperature***Not Applicable***Viscosity***Not Applicable***Molecular weight***Not Applicable***SECTION 10: Stability and reactivity**

**10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

None known.

**10.5. Incompatible materials**

None known.

**10.6. Hazardous decomposition products****Substance**

Hydrogen Fluoride

**Condition**

At Elevated Temperatures

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

No health effects are expected.

**Carcinogenicity:**

| Ingredient                                                      | CAS No.    | Class Description              | Regulation                                  |
|-----------------------------------------------------------------|------------|--------------------------------|---------------------------------------------|
| Silica, Crystalline (Respirable Size)                           | 14808-60-7 | Known To Be Human Carcinogen.  | National Toxicology Program Carcinogens     |
| Silica dust, crystalline, in the form of quartz or cristobalite | 14808-60-7 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Titanium dioxide                                                | 13463-67-7 | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |

**Additional Information:**

This document covers only the product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered. This product contains titanium dioxide and quartz (crystalline) silica. Cancer of the lungs has been associated with inhalation of high levels of titanium dioxide in animal studies, and occupational exposure to inhaled quartz silica has been associated with silicosis and lung cancer. No exposure to titanium dioxide or quartz silica is expected during the normal handling and use of this product. Titanium dioxide and quartz silica were not detected when air sampling was conducted during simulated use of similar products containing these substances. Therefore, the health effects associated with titanium dioxide and quartz (crystalline) silica are not expected during the normal use of this product.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name                                                                | Route                          | Species           | Value                                          |
|---------------------------------------------------------------------|--------------------------------|-------------------|------------------------------------------------|
| Overall product                                                     | Dermal                         |                   | No data available; calculated ATE >5,000 mg/kg |
| Overall product                                                     | Inhalation-Dust/Mist(4 hr)     |                   | No data available; calculated ATE >12.5 mg/l   |
| Overall product                                                     | Ingestion                      |                   | No data available; calculated ATE >5,000 mg/kg |
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Dermal                         |                   | LD50 estimated to be > 5,000 mg/kg             |
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Inhalation-Dust/Mist (4 hours) | Rat               | LC50 > 2.3 mg/l                                |
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Ingestion                      | Rat               | LD50 > 5,000 mg/kg                             |
| Inorganic Fluoride 1                                                | Dermal                         |                   | LD50 estimated to be > 5,000 mg/kg             |
| Inorganic Fluoride 1                                                | Inhalation-Dust/Mist (4 hours) | Rat               | LC50 > 5.3 mg/l                                |
| Inorganic Fluoride 1                                                | Ingestion                      | Rat               | LD50 5,854 mg/kg                               |
| Filler 1                                                            | Dermal                         | Rat               | LD50 > 2,000 mg/kg                             |
| Filler 1                                                            | Inhalation-Dust/Mist (4 hours) | Rat               | LC50 3 mg/l                                    |
| Filler 1                                                            | Ingestion                      | Rat               | LD50 6,450 mg/kg                               |
| Inorganic Fluoride 2                                                | Dermal                         | Rabbit            | LD50 > 2,100 mg/kg                             |
| Inorganic Fluoride 2                                                | Inhalation-Dust/Mist (4 hours) | Rat               | LC50 4.5 mg/l                                  |
| Inorganic Fluoride 2                                                | Ingestion                      | Rat               | LD50 > 5,000 mg/kg                             |
| Filler 2                                                            | Ingestion                      | Rat               | LD50 > 5,000 mg/kg                             |
| Filler 2                                                            | Dermal                         | similar compounds | LD50 > 5,000 mg/kg                             |
| Filler 2                                                            | Inhalation-Dust/Mist (4 hours) | similar compounds | LC50 > 2.08 mg/l                               |
| Inorganic Fluoride 3                                                | Dermal                         | Rabbit            | LD50 > 2,100 mg/kg                             |

|                      |                                |        |                                    |
|----------------------|--------------------------------|--------|------------------------------------|
| Inorganic Fluoride 3 | Inhalation-Dust/Mist (4 hours) | Rat    | LC50 4.5 mg/l                      |
| Inorganic Fluoride 3 | Ingestion                      | Rat    | LD50 5,000 mg/kg                   |
| Titanium Dioxide     | Dermal                         | Rabbit | LD50 > 10,000 mg/kg                |
| Titanium Dioxide     | Inhalation-Dust/Mist (4 hours) | Rat    | LC50 > 6.82 mg/l                   |
| Titanium Dioxide     | Ingestion                      | Rat    | LD50 > 10,000 mg/kg                |
| Quartz Silica        | Dermal                         |        | LD50 estimated to be > 5,000 mg/kg |
| Quartz Silica        | Ingestion                      |        | LD50 estimated to be > 5,000 mg/kg |

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

| Name                                                                | Species                 | Value                     |
|---------------------------------------------------------------------|-------------------------|---------------------------|
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Rabbit                  | No significant irritation |
| Inorganic Fluoride 1                                                | Rabbit                  | No significant irritation |
| Filler 1                                                            | Rabbit                  | No significant irritation |
| Inorganic Fluoride 2                                                | Multiple animal species | No significant irritation |
| Filler 2                                                            | similar compounds       | No significant irritation |
| Inorganic Fluoride 3                                                | Multiple animal species | No significant irritation |
| Titanium Dioxide                                                    | Rabbit                  | No significant irritation |
| Quartz Silica                                                       | Professional judgment   | No significant irritation |

### Serious Eye Damage/Irritation

| Name                                                                | Species           | Value                     |
|---------------------------------------------------------------------|-------------------|---------------------------|
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Rabbit            | No significant irritation |
| Inorganic Fluoride 1                                                | Rabbit            | No significant irritation |
| Filler 1                                                            | Rabbit            | No significant irritation |
| Inorganic Fluoride 2                                                | Rabbit            | Mild irritant             |
| Filler 2                                                            | similar compounds | Mild irritant             |
| Inorganic Fluoride 3                                                | Rabbit            | Mild irritant             |
| Titanium Dioxide                                                    | Rabbit            | No significant irritation |

### Skin Sensitization

| Name             | Species          | Value          |
|------------------|------------------|----------------|
| Filler 2         | Human            | Not classified |
| Titanium Dioxide | Human and animal | Not classified |

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

| Name                                                                | Route    | Value         |
|---------------------------------------------------------------------|----------|---------------|
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | In Vitro | Not mutagenic |
| Filler 2                                                            | In Vitro | Not mutagenic |

|                  |          |                                                                              |
|------------------|----------|------------------------------------------------------------------------------|
| Filler 2         | In vivo  | Not mutagenic                                                                |
| Titanium Dioxide | In Vitro | Not mutagenic                                                                |
| Titanium Dioxide | In vivo  | Not mutagenic                                                                |
| Quartz Silica    | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica    | In vivo  | Some positive data exist, but the data are not sufficient for classification |

### Carcinogenicity

| Name                                                                | Route      | Species                 | Value            |
|---------------------------------------------------------------------|------------|-------------------------|------------------|
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Inhalation | Rat                     | Not carcinogenic |
| Titanium Dioxide                                                    | Ingestion  | Multiple animal species | Not carcinogenic |
| Titanium Dioxide                                                    | Inhalation | Rat                     | Carcinogenic     |
| Quartz Silica                                                       | Inhalation | Human and animal        | Carcinogenic     |

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

| Name     | Route     | Value                          | Species                 | Test Result           | Exposure Duration            |
|----------|-----------|--------------------------------|-------------------------|-----------------------|------------------------------|
| Filler 1 | Ingestion | Not classified for development | Rat                     | NOAEL 625 mg/kg/day   | premating & during gestation |
| Filler 2 | Ingestion | Not classified for development | Multiple animal species | NOAEL 1,600 mg/kg/day | during organogenesis         |

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

| Name     | Route      | Target Organ(s)    | Value          | Species | Test Result      | Exposure Duration |
|----------|------------|--------------------|----------------|---------|------------------|-------------------|
| Filler 1 | Inhalation | respiratory system | Not classified | Rat     | NOAEL 0.812 mg/l | 90 minutes        |

#### Specific Target Organ Toxicity - repeated exposure

| Name                                                                | Route      | Target Organ(s)                 | Value                                                                        | Species          | Test Result          | Exposure Duration     |
|---------------------------------------------------------------------|------------|---------------------------------|------------------------------------------------------------------------------|------------------|----------------------|-----------------------|
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Inhalation | pneumoconiosis                  | Some positive data exist, but the data are not sufficient for classification | Human            | NOAEL Not available  | occupational exposure |
| Ceramic Aluminum Oxide / Aluminum Oxide Mineral Blend (non-fibrous) | Inhalation | pulmonary fibrosis              | Not classified                                                               | Human            | NOAEL Not available  | occupational exposure |
| Filler 1                                                            | Inhalation | respiratory system              | Not classified                                                               | Human            | NOAEL Not available  | occupational exposure |
| Inorganic Fluoride 2                                                | Inhalation | bone, teeth, nails, and/or hair | Causes damage to organs through prolonged or repeated exposure               | Rat              | NOAEL 0.0005 mg/l    | 5 months              |
| Inorganic Fluoride 2                                                | Inhalation | respiratory system              | Causes damage to organs through prolonged or repeated exposure               | Rat              | NOAEL 0.00021 mg/l   | 90 days               |
| Inorganic Fluoride 2                                                | Ingestion  | bone, teeth, nails, and/or hair | Causes damage to organs through prolonged or repeated exposure               | Rat              | LOAEL 0.58 mg/kg/day | 14 weeks              |
| Filler 2                                                            | Inhalation | respiratory system              | Not classified                                                               | Human            | NOAEL Not available  | occupational exposure |
| Filler 2                                                            | Inhalation | pulmonary fibrosis              | Not classified                                                               | Human and animal | NOAEL Not available  |                       |
| Filler 2                                                            | Ingestion  | liver   kidney and/or bladder   | Not classified                                                               | Rat              | NOAEL 2,500          | 2 years               |

|                      |            |                                 |                                                                              |       |                      |                       |
|----------------------|------------|---------------------------------|------------------------------------------------------------------------------|-------|----------------------|-----------------------|
|                      |            | hematopoietic system            |                                                                              |       | mg/kg/day            |                       |
| Inorganic Fluoride 3 | Inhalation | bone, teeth, nails, and/or hair | Causes damage to organs through prolonged or repeated exposure               | Rat   | NOAEL 0.0005 mg/l    | 5 months              |
| Inorganic Fluoride 3 | Inhalation | respiratory system              | Causes damage to organs through prolonged or repeated exposure               | Rat   | NOAEL 0.00021 mg/l   | 90 days               |
| Inorganic Fluoride 3 | Ingestion  | bone, teeth, nails, and/or hair | Causes damage to organs through prolonged or repeated exposure               | Rat   | LOAEL 0.58 mg/kg/day | 14 weeks              |
| Titanium Dioxide     | Inhalation | respiratory system              | Some positive data exist, but the data are not sufficient for classification | Rat   | LOAEL 0.01 mg/l      | 2 years               |
| Titanium Dioxide     | Inhalation | pulmonary fibrosis              | Not classified                                                               | Human | NOAEL Not available  | occupational exposure |
| Quartz Silica        | Inhalation | silicosis                       | Causes damage to organs through prolonged or repeated exposure               | Human | NOAEL Not available  | occupational exposure |

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Combustion products will include HF. Facility must be capable of handling halogenated materials.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Not applicable

**Health Hazards**

Not applicable

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):****Ingredient**Ceramic Aluminum Oxide / Aluminum Oxide  
Mineral Blend (non-fibrous)**C.A.S. No**

1344-28-1

**% by Wt**

10 - 35

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.****SECTION 16: Other information****NFPA Hazard Classification****Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride. During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

**Document Group:** 43-0450-7**Issue Date:** 05/13/25**Version Number:** 2.00**Supersedes Date:** 04/14/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**