



**DURATEC™ PREMIUM REINFORCED NON-DETECTABLE TAPE 3” x 6000’**

Premier non-detectable woven polyethylene tape for the "Last Line of Defense" against third party damage. Patented reinforcing weave provides the strength needed for plowed-in installations. Will not stretch when dug into; the printed message stays intact and is easy to read. DuraTec leads the field as the strongest, patented, non-distorting warning tape ever engineered to prevent dig-ins.

**INCLUDES:**

- (1) [DURATEC™ PREMIUM REINFORCED NON-DETECTABLE TAPE \(28-031\)](#)

**FEATURES:**

- Environmentally safe
- Lead free
- Permanent messaging
- Wear resistant

**PRODUCT SPECIFICATIONS:**

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	7.0 mil (Nominal)	0.175 mm
Weight	ASTM D-2103	22.46 lbs / 1,000 ft <sup>2</sup>	10.97 kg / 100 m <sup>2</sup>
Tensile Strength	ASTM D-882	Length: 10,620 psi	Length: 73.22 Mpa
Elongation	ASTM D-882	Length: 38%	Length: 38%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		.692 g/cc