



品质铸造品牌 创新成就未来

Quality Found the Brand Innovation Achieve the Future

## MATERIAL SAFETY DATA SHEET

Product Name: Lithium-Ion Battery

Approved By	Checkup
Zhang Shenjiang	Wang Yong
DATE: 2023-12-22	DATE: 2023-12-22

## MATERIAL SAFETY DATA SHEET

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION: Lithium-Ion Battery

MANUFACTURER: ChangHong Grand-Pro Tech Co.,Ltd.

ADDRESS: Intersection of Shihu Ave. and Linjing 2nd Rd. SuXian District, Chenzhou, Hunan, China.

valid period : 31th Dec 2024

Tel: (86)735-2668188

Fax: (86)735-2668799



### 2. COMPOSITION INFORMATION

Ingredient	Concentration	CAS No.	EC No.
Cobalt lithium mangancsc nickel oxide	< 45%	346417-97-8	620-032-4
Carbon (cathode)	<26%	7440-44-0	231-153-3
Electrolyte (EMC/PC/EC/LiPF6)	< 14%	623-53-0/108-32-7/96-49-1/21324-40-3	433-480-9/203-572-1/202-510-0/244-334-7
Copper foil	2-10%	7440-50-8	231-159-6
Aluminum foil	4-5%	7429-90-5	231-072-3
Polyvinylidene fluoride	< 1%	24937-79-9	607-458-6

### 3. HAZARDS IDENTIFICATION

#### Emergency Overview (including Signs and Symptoms, Route(s) of Entry, etc.)

Intact batteries present no specific hazards.

#### Acute Health Hazards (e.g., Inhalation, Eye Contact, Skin Contact, Ingestion, etc.):

Burning batteries: AVOID inhalation of toxic fumes. Burning batteries emit toxic fumes, which are irritating to the lungs.

Leaking batteries: AVOID exposure to leaking electrolyte, it can cause severe irritation and/or damage to the skin, mucous membrane or eyes.

Address: Intersection of Shihu Ave. and Linjing 2nd Rd. SuXian District, Chenzhou, Hunan, China

Tel: (86) 735-2668188 Fax: (86) 735-2668799

**Product Name: Lithium-Ion Battery**

Material Safety Data Sheet

File number and version:GLB/YZM2401-A0

**Chronic Health Effects** (e.g., Carcinogenicity, Teratology, Reproduction, Mutagenicity, etc.):

Cobalt: Suspected human carcinogenic agent.

**Medical Conditions Generally Aggravated by Exposure: None.**

**4. FIRST AID MEASURES****INGESTION**

If swallowed, obtain medical attention immediately.

**INHALATION**

If battery is burning, leave the area immediately. If exposed to fumes, seek medical attention promptly.

**EYE CONTACT**

Rinse eyes with water for 15 minutes and seek medical attention.

**SKIN CONTACT**

If battery electrolyte leaks on to the skin flush the affected area for at least 15 minutes with clean water. DO NOT attempt to neutralize. Seek medical attention promptly.

**INGESTION**

Drink milk/water and induce vomiting; seek medical attention.

**5. FIRE FIGHTING MEASURES**

**Flammable Properties:** N/A

**Flashpoint:** Method:

**Autoignition Temperature:**

**Flammable Limits:** N/A

**Lower flammable limit:** Upper flammable limit:

**Hazardous Combustion Products:** Burning batteries may emit acrid smoke irritating fumes, and toxic fumes of fluoride.

**Extinguishing Media:** Carbon dioxide (CO<sub>2</sub>) or dry chemical fire extinguisher, 10-B: C.

**Fire Fighting Instructions:**

**Personnel:** Fight the fire in a defensive mode, while exiting the area. When using a CO<sub>2</sub> fire extinguisher, DO NOT re-enter the area until it has been thoroughly ventilated (i.e., purged) of the CO<sub>2</sub> extinguishing agent.

**Firefighters:** Use a self-contained breathing apparatus (SCBA).

**6. ACCIDENTAL RELEASE MEASURES**

**Small Spill:** If batteries show signs of leaking, AVOID skin or eye contact with the material leaking from the battery. Use chemical resistant rubber gloves and non-flammable absorbent materials for clean-up.

On Land

Address: Intersection of Shihu Ave. and Linjing 2nd Rd. SuXian District, Chenzhou, Hunan, China

Tel: (86) 735-2668188 Fax: (86) 735-2668799

**Product Name: Lithium-Ion Battery**

Material Safety Data Sheet

File number and version:GLB/YZM2401-A0

Place material into suitable containers and call local fire/police department.

In Water

If possible, remove from water and call local fire/police department.

**7. HANDLING AND STORAGE**

Handling: Recharge batteries IAW methods specified in applicable technical manuals.

DO NOT:

Overcharge this battery.

Abuse, mutilate or short circuit the battery.

Storage: Gain approval for storage areas from the Installation Fire Department. Store batteries in a cool

(i.e.,  130 F), dry and well ventilated area.

DO NOT:

Store batteries in direct sunlight or under hot conditions.

Soak and keep batteries away from open flame or heat.

Store batteries in the same stacks with hazardous materials.

Store batteries in office areas, or other areas where personnel congregate.

Work/Hygienic Practices: Thoroughly wash hands after cleaning-up a battery spill (i.e., leaking or venting batteries). NO eating, drinking or smoking in battery storage areas.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****ENGINEERING CONTROLS**

Keep away from heat and open flame. Store in a cool dry place.

**PERSONAL PROTECTION**

Respirator: Not required during normal operations. SCBA required in the event of a fire.

Eye/face protection: Not required beyond safety practices of employer.

Gloves: Not required for handling of cells.

Foot protection: Steel toed shoes recommended for large container handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Point @ 760 mm Hg (°C): NA

Vapor Pressure (mm Hg @ 25°C): NA

Vapor Density (Air = 1): NA

Density (grams/cc): NA

Percent Volatile by Volume (%): NA

Evaporation Rate (Butyl Acetate = 1): NA

Physical State: NA

Solubility in Water (% by Weight): NA

pH: NA

Address: Intersection of Shihu Ave. and Linjing 2nd Rd. SuXian District, Chenzhou, Hunan, China

Tel: (86) 735-2668188 Fax: (86) 735-2668799

Appearance and Odor: geometric solid object

## 10. STABILITY AND REACTIVITY

### REACTIVITY

None

### INCOMPATIBILITIES

None during normal operation. Avoid exposure to heat, open flame, and corrosives.

### HAZARDOUS DECOMPOSITION PRODUCTS

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

### CONDITIONS TO AVOID

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

## 11. TOXICOLOGICAL INFORMATION

This product does not elicit toxicological properties during routine handling and use.

Sensitization	Teratogenicity	Reproductive toxicity	Acute toxicity
NO	NO	NO	NO

This product does not contain any kinds of the following substances and halogen-type flame retardants including Chlorine and Bromide type harmful flame retardants which are listed in Appendix of TCO documents and relevant international ECO requirements:

Polybromated Biphenyls	(PBB)
Polybromated Biphenyl Ethers	(PBBE)
Polybromated Biphenyl Oxides	(PBBO)
Polybromated Diphenylethers	(PBDE)
Polychlorinated Biphenyl	(PCB)
Polychloronated Diphenylethers	(PCDE)
Tetrabromophisphenol A	(TBBPA)
Asbestos, Antimonytrioxide, Dioxine	

None of the following substances will be exposed, leaked, or emitted during transportation,

storage or any operation and any temperature condition:

Chlorinated Fluorohydrocarbon (FCKW)

Acrylonitrile

Styrol Phenol Benzol

Mercury of greater than 0.0001 wt% for alkaline battery

Mercury of greater than 0.0005 wt% for other battery

Lithium content of greater than 0.5g/battery cell Cadmium, lead, and other harmful heavy metal

This product does not contain mercury and lithium-metal.

Mercury content:<

Lithium-Ion content:<

Address: Intersection of Shihu Ave.and Linjing 2nd Rd.SuXian District, Chenzhou, Hunan,China

Tel: (86) 735-2668188 Fax: (86) 735-2668799

**Product Name: Lithium-Ion Battery**

Material Safety Data Sheet

File number and version:GLB/YZM2401-A0

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

**12. ECOLOGICAL INFORMATION**

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

**13. DISPOSAL INFORMATION**

Recommended methods for safe and environmentally preferred disposal :

**Product(waste from residues)**

Do not throw out a used battery cell. Recycle it through the recycling company.

**Contaminated packaging**

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates, dispose as industrial wastes subject to special control.

RCRA Waste Code: Nonregulated

Dispose of according to all federal, state, and local regulations.

**14. TRANSPORTATION INFORMATION**

In the case of transportation, confirm no leakage and no overspill from a container. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to Section 7-HANDLING AND STORAGE also. We regard to air transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions;
- The International Air Transport Association(IATA) Dangerous Goods Regulations(65<sup>th</sup> Edition 2024: complies with current IATA packing instruction of PI965- 967);
- The International Maritime Dangerous Goods(IMDG) Code;
- The US Hazardous Materials Regulation(HMR) pursuant to a final rule issued by RSPA
- The Office of Hazardous Materials Safety within the US Department of Transportation's Research and Special Programs Administration(RSPA), and The UN Recommendations on the Transport of Dangerous Goods Model Regulations and the Manual of Tests and Criteria.
- The results of the UN Recommendation on the Transport of Dangerous Goods

Manual of Test and Criteria (38.3 Lithium battery)		Test Results	Remark
No.	Test Item		
T1	Altitude Simulation	Pass	
T2	Thermal Test	Pass	
T3	Vibration	Pass	

Address: Intersection of Shihu Ave.and Linjing 2nd Rd.SuXian District, Chenzhou, Hunan,China

Tel: (86) 735-2668188 Fax: (86) 735-2668799

**Product Name: Lithium-Ion Battery**

Material Safety Data Sheet

File number and version:GLB/YZM2401-A0

T4	Shock	Pass	
T5	External Short Circuit	Pass	
T6	Impact	Pass	
T7	Overcharge	Pass	For Pack Only
T8	Forced Discharge	Pass	For Pack Only

However, since it corresponds to IATA-DGR, this battery cell can be conveyed normally.

Our batteries conform to conform to the international air transport association pi965-967 packing instruction.

**15. REGULATORY INFORMATION**

OSHA hazard communication standard (29 CFR 1910.1200)

Hazardous  N0-hazardous

**16. OTHER LNFORMATION**

The information above is believed to be accurate and represents the best infrmation currently available to us. However, Grand-Pro makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determinie the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration. This material safety data sheet provides guidelines for the safe handling and use of this product, it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

\*\*\*\*\*The End\*\*\*\*\*